

FEDERAL®

TIRES

4x4 & SUV Tires / ADVENTURE EXPLORING

COURAGIA M/T

The mighty **Couragia M/T** is legendary for its toughness, maximum off-road traction, and deep-biting tread blocks.

Reinforced compounds contribute to exceptional durability against cuts, chips, and abrasions.

Aggressive tread design and strengthened shoulder deliver excellent traction and protection from off-road impact.

Optimized block design increases off-road traction and control.

Uniquely designed incremental block edge quickly sheds dirt, sand, and gravel for ultimate off-road traction.



4x4



Light Truck



Rugged Terrain



Off Road



All season

M+S

ADVENTURE EXPLORING

Federal's versatile SUV and 4x4 tires offer ultimate traction and steering control to handle on-road or off-road expeditions.



Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim in	Approved Rim Width in	Tread Width mm	Tread Depth		Weight KG	MAX. PSI COLD	Max Load KGS	Sidewall Type
			mm	in	mm	in				in32"	mm				
30*9.50R15	6	104Q	757	29.8	252	9.9	7.5	6.5-8.5	192	19	15	20.1	50	900	OWL
31*10.50R15	6	109Q	785	30.9	268	10.6	8.5	7-9	200	19	15	22.7	50	1030	OWL
33*12.50R15	6	108Q	833	32.8	325	12.8	10	8.5-11	248	19	15	28.9	35	1000	OWL
33*12.50R20	10	114Q	833	32.8	313	12.3	10	9.5-10.5	256	21	16.7	30.2	65	1180	BSW
35*12.50R15	6	113Q	883	34.8	343	13.5	10	9.5-10.5	252	21	16.7	29.8	35	1150	BSW
35*12.50R20	10	121Q	883	34.8	318	12.5	10	8.5-11	256	21	16.3	32.7	65	1450	BSW
205/80R16	8	110/108Q	734	28.9	210	8.3	5.5	5-7	160	19	15	17.5	65	1060/1000	OWL
225/75R16	10	115/112Q	752	29.6	215	8.4	6	6-7	160	19	15	18	80	1215/1120	BSW
235/75R15	6	104/101Q	734	28.9	228	9	6.5	6-7	168	19	15	17.4	50	900/ 825	OWL
235/85R16	10	120/116Q	806	31.7	231	9.1	6.5	6-7.5	170	19	15	21.6	80	1400/1260	OBL
245/75R16	10	120/116Q	781	30.7	244	9.6	6	6.5-8	178	19	15	21.5	80	1400/1260	BSW
265/70R17	10	121/118Q	810	31.9	272	10.7	8	7-8.5	212	20	15.9	26.4	80	1450/1320	OWL
265/75R16	8	119/116Q	807	31.8	260	10.2	7.5	7-8	193	19	15	24.4	65	1360/1250	OWL
275/65R18	8	119/116Q	824	32.4	275	10.8	8	7.5-9	216	20	15.6	23.3	65	1360/1250	BSW
285/70R17	8	121/118Q	840	33.1	287	11.3	8.5	8-9	228	20	15.9	26.1	65	1450/1320	OWL
285/70R17	8	121/118Q	840	33.1	287	11.3	8.5	8-9	228	20	15.9	26.1	65	1450/1320	OWL

These data can be changed by the manufacturer without prior notice and differently applied by regions.

