

FEDERAL®

TIRES

PCR Tires / PREMIUM TOURING

FORMOZA GIO

Engineered for maximum fuel efficiency, the low-rolling-resistance **Formoza GIO** provides all-season traction and comfortable rides.

Enclosed tread and tire blocks reduce contact noise for comfortable rides.

Heat dissipation compounds and honeycomb design on sidewall minimize heat generation and rolling resistance for improved fuel efficiency.

Blade-shaped tread grooves channel water effectively, ensuring safe rides on slippery roads.



Micro



Compact



Sedan



Quiet ride



Fuel Efficiency



Street



All season

M+S

PREMIUM TOURING

Federal's premium touring tires offer excellent all-season driving pleasure, comfort, safety, and value.



Size	LI/SS	Overall Diameter mm	Section Width mm	Standard Rim in	Approved Rim Width in	Tread Width mm	Tread Depth mm	Weight KG	MAX. PSI COLD	Max Load KGS	UTQC	RR	Wet Grip	(dBS)	E_Sound
155/65R13	73T	534	152	4.5	4.5-5.5	114	6.2	5.5	44	365	420A A	E	B	70	2
155/70R13	75T	547	153	4.5	4-5	113	7.3	5.8	44	387	420A A	E	B	70	2
155/80R13	79T	577	159	4.5	4-5	113	7	6.3	44	437	420A A	E	B	70	2
165/60R14	75H	558	165	5	4.5-6	122	6.6	6.2	44	387	420A A	E	B	70	2
165/65R13	77H	546	168	5	4.5-6	124	6.2	6.1	44	412	420A A	E	B	70	2
165/65R14	79T	575	168	5	4.5-6	124	6.2	6.3	44	437	420A A	E	B	70	2
165/70R13	79T	560	165	5	4-5.5	122	7.3	6.3	44	437	420A A	E	B	70	2
165/70R14	81T	584	166	5	4-5.5	120	7.3	6.7	44	462	420A A	E	B	70	2
175/60R14	79H	564	176	5	5-6	127	7	6.6	44	437	420A A	E	B	70	2
175/65R13	80T	556	177	5	5-6	128	7.2	6.4	44	450	420A A	E	B	70	2
175/65R14	82H	582	176	5	5-6	128	7.2	6.8	44	475	420A A	E	B	70	2
175/70R13	82H	575	175	5	4.5-6	127	7.5	6.9	44	475	420A A	E	B	70	2
175/70R14	84H	599	175	5	4.5-6	125	7.5	7	44	500	420A A	E	B	70	2
185/60R14	82H	578	189	5.5	5-6.5	136	7.4	7.1	44	475	420A A	E	C	71	2
185/60R15	84H	609	187	5.5	5-6.5	140	7.9	7.6	44	500	420A A	E	C	71	2
185/65R14	86H	598	191	5.5	5-6.5	138	7.2	7.8	44	530	420A A	E	C	71	2
185/65R15	88H	626	190	5.5	5-6.5	138	7.2	8.1	44	560	420A A	E	C	71	2
185/70R14	88H	612	186	5.5	4.5-6	134	7.9	7.7	44	560	420A A	E	C	71	2
195/60R15	88H	621	197	6	5.5-7	144	7.4	8.4	44	560	420A A	E	C	71	2
195/65R14	89H	609	199	6	5.5-7	144	7.2	8	44	580	420A A	E	C	71	2
195/65R15	91H	633	199	6	5.5-7	144	7.2	9.5	44	615	420A A	E	C	71	2
195/65R15	95T XL	632	204	6	5.5-7	144	7.2	9.3	50	690	420A A	E	C	71	2
195/70R14	91H	626	197	6	5-6.5	142	7.9	8.4	44	615	420A A	E	C	71	2
205/60R15	91H	629	208	6	5.5-7.5	150	7.7	8.5	44	615	420A A	E	C	71	2
205/60R16	92H	657	204	6	5.5-7.5	150	7.7	9.9	44	630	420A A	E	C	71	2
205/65R15	95H	648	209	6	5.5-7	150	7.6	9.8	44	690	420A A	E	C	71	2
215/60R16	95H	668	218	6.5	6-7.5	167	7.7	10.6	44	690	420A A	E	C	71	2
215/65R15	96H	659	221	6.5	6-7.5	160	7.6	9.8	44	710	420A A	E	C	71	2
225/60R15	96V	651	222	6.5	6-8	173	8	10.2	44	710	420A A	E	C	71	2
225/60R16	98H	673	227	6.5	6-8	173	8	10.7	44	750	420A A	E	C	71	2

These data can be changed by the manufacturer without prior notice and differently applied by regions.

