

FEDERAL®

TIRES

4x4 & SUV Tires / ADVENTURE EXPLORING

XPLORA MTS

The **Xplora MTS** appeals to swag pickup tuning enthusiasts who crave for center of attention and sporty driving performance!

Subtle, V-shaped sipes enhance tire block rigidity and prevent sharp stones from attaching to the tire's tread surface.

Bulky armor-appearance tread patterns and massive tire blocks provide superb steering and traction.

Wide, unidirectional grooves disperse water effectively and reduce noise for comfort ride.

Linear shoulder blocks improve aerodynamics for better steering control and comfort.

"NO OFF-ROAD USE"



4x4



Light Truck



Performance



Directional



Street



ADVENTURE EXPLORING

Federal's versatile SUV and 4X4 tires offer ultimate traction and steering control to handle on-road or off-road expeditions.



Size	PR	LI/SS	Overall Diameter mm	Section Width mm	Standard Rim in	Approved Rim Width in	Tread Width mm	Tread Depth mm	Weight KG	MAX. PSI COLD	Max Load KGS	Sidewall Type
33*12.50R20LT	10	114Q	830	306	10	8.5-11	254	20	31.1	65	1180	BSW
33*12.50R22LT	10	114Q										
35*12.50R20LT	10	121Q	878	326	10	8.5-11	251	21	35.7	65	1450	N/A
35*12.50R22LT	10	117Q	878	311	10	8.5-11	254	20	32.7	65	1285	N/A
35*12.50R24LT	10	114Q	881	305	10	8.5-11	258	20	21.5	65	1180	N/A
37*12.50R22LT	10	123Q	930	326	10	9-11.5	254	20	36.9	65	1550	N/A
37*13.50R22LT	10	123Q	929	350	11	8.5-11	273	20	37.7	65	1550	N/A
37*13.50R24LT	10	120Q	930	334	11	8.5-11	273	20	37.3	65	1400	N/A
38*15.50R24LT	10	127P	956	384	12.5	11-14	320	21	42.9	65	1750	N/A
40*15.50R22LT	10	128Q	1008	402	12.5	11-14	312	22	42.2	65	1800	N/A
40*15.50R24LT	10	128P	1006	394	12.5	11-14	312	22	43.5	65	1800	N/A
42*15.50R24LT	8	130Q	1059	401	12.5	11-14	312	21	45.1	50	1900	N/A
LT265/70R17	10	121/118Q	808	279	8	7-8.5	218	20	20.3	80	1450/1320	BSW
LT265/70R18	10	124/121Q	834	276	8	7-9	218	20	29.9	80	1600/1450	BSW
LT275/65R18	10	123/120Q	819	278	8	7.5-9	223	20	30.4	80	1550/1400	BSW
LT275/70R18	10	125/122Q	849	283	8	7-9	223	20		80	1650/1500	BSW
LT285/70R17	10	121/118Q	835	302	8.5	7.5-9	234	20	33.4	80	1450/1320	BSW
LT315/70R17	10	121/118Q	875	337	9.5	8-11	258	20	37.3	65	1450/1320	BSW

These data can be changed by the manufacturer without prior notice and differently applied by regions.

